



# Reach-Ins & Pass-Thrus

REFRIGERATORS & FREEZERS



**Continental**<sup>®</sup>  
Refrigerator

INNOVATIVE DESIGNS FOR YOUR FOODSERVICE NEEDS

# Reach-Ins & Pass-Thrus

---

## Refrigerators & Freezers

Our Reach-In Refrigerators and Freezers are designed for performance and reliability that protects your long-term investment. We use the highest quality materials and components to provide the user with optimal product temperatures, exceptional food safety and the best value in today's foodservice market.

## State-of-the-Art Designs

Continental Refrigerator has one of the most diversified commercial Reach-In product lines in the industry, with modern styling and standard features not found on other units.

## Performance & Reliability

Performance-run tested for a minimum of 12 hours providing a highly sophisticated temperature analysis recording, exclusive to each cabinet.



# FLEXIBILITY

## Modifications Made Easy.

At Continental Refrigerator, we know the foodservice industry is an ever-changing environment. We are reminded of this every day through feedback from our customers, both directly and through our network of representatives. In fact, customer feedback has often lead to our custom engineering modifications becoming standard product features.

For this reason, we pride ourselves in delivering feature-rich refrigeration equipment solutions designed specifically for the commercial foodservice market. Whether it's kitchen ambient, food safety, limited space or storage challenges, our products are packed with flexible options that provide **real** operator benefits out of the box. This flexibility, a key differentiator of our products, enables our customers to modify base product features strategic to the way they operate their kitchen or bar environment.

### Shown: 2RN

Standard Model



Half Doors



Laminated Doors



Half Doors (On Right Only),  
Pan Slide Assemblies (On Right)

Glass Doors

6" Adjustable Legs

*Consult factory for other modifications*

## Overview of Models & Standard Features

### Standard Features

Stainless steel front, aluminum end panels and interior

Self-contained, performance-rated refrigeration system

**Natural, Low GWP, Environmentally-safe R-290 refrigerant**

3" Non-CFC polyurethane foam insulation

Smooth, polished, chrome door handles (solid doors)

Cam-action, lift-off hinges

Heavy-duty, epoxy-coated steel shelves

Automatic, electric condensate evaporator

Magnetic, snap-in Santoprene™ door gaskets

Door locks

Snap-in door wiper (sliding glass doors)

5" high casters

Self-closing doors

LED interior lighting

Electronic controller w/ digital display & hi-low alarm

Automatic electric defrost (freezers/dual temp freezer section)

Triple-pane, tempered glass doors (hinged glass doors)


Double-pane, low-e, tempered glass doors (sliding glass doors)

High-efficiency PVC frame (sliding glass doors)


### Widths




Slim Line  
1 Section  
17 3/4"




Slim Line  
2 Section  
36 1/4"




Standard  
1 Section  
26"




Standard  
2 Section  
52"




Standard  
3 Section  
78"




Extra-Wide (X)  
1 Section  
36 1/4"



Extra-Wide  
1 Section  
28 1/2"




Extra-Wide  
2 Section  
57"




Extra-Wide  
3 Section  
85 1/2"


### Depths



Standard Depth  
Reach-In  
35 3/8"




Shallow Depth  
Reach-In  
29 1/4"



Standard Depth  
Pass-Thru  
38 3/4"


### Door Styles




Hinged Solid  
Full Door




Hinged Solid  
Half Doors




Hinged Glass  
Full Door



Hinged Glass  
Half Doors




Sliding Glass  
Full Doors




Sliding Glass  
Half Doors


### Optional Pan Slide Assemblies (not available for Shallow Depth models)




Stainless Steel Full & Half Section  
for 18 x 26 or (2) 18 x 14 Pans  
on 3" Center Bottom Supports  
Holds (# pans/section): 16 (full), 8 (half)




Stainless Steel Full & Half Section  
for 18 x 26 or (2) 18 x 14 Pans  
on 3" Center Rim Supports  
Holds (# pans/section): 16 (full), 8 (half)



**Extra-Wide (E) Models Only**  
Universal Stainless Steel Full & Half Section  
for (1) 18 x 26 or (2) 12 x 20 Pans  
on 5" Center Bottom Supports  
Holds (# pans/section): 10 (full), 5 (half)



Chrome-Plated Wire Full & Half Section  
for 18 x 26 Pans on 2" Center Rim Supports  
Holds (# pans/section): 21 (full),  
9 top & 12 bottom (half)



Chrome-Plated Wire Full & Half Section  
for 18 x 26 Pans on 2" Center Bottom Supports  
Holds (# pans/section): 21 (full),  
9 top & 12 bottom (half)

### Optional Models:

-SA: Stainless steel exterior, aluminum interior  
-SS: Stainless steel exterior & interior

# Specifications - Standard & Slim Line Refrigerators

## Standard Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1RN	1RNSA	1RNSS	26 x 35 3/8 x 82 1/4	1940	1/4+	310
	2RN	2RNSA	2RNSS	52 x 35 3/8 x 82 1/4	2560	1/3+	520
	3RN	3RNSA	3RNSS	78 x 35 3/8 x 82 1/4	4010	1/2	725
HALF DOORS	1RNHD	1RNSAHD	1RNSSH	26 x 35 3/8 x 82 1/4	1940	1/4+	310
	2RNHD	2RNSAHD	2RNSSH	52 x 35 3/8 x 82 1/4	2560	1/3+	520
	3RNHD	3RNSAHD	3RNSSH	78 x 35 3/8 x 82 1/4	4010	1/2	725
FULL DOORS SHALLOW DEPTH	1RSN	1RSNSA	1RSNSS	26 x 29 1/4 x 82 1/4	1940	1/4+	310
	2RSN	2RSNSA	2RSNSS	52 x 29 1/4 x 82 1/4	2560	1/3+	520
	3RSN	3RSNSA	3RSNSS	78 x 29 1/4 x 82 1/4	4010	1/2	725
HALF DOORS SHALLOW DEPTH	1RSNHD	1RSNSAHD	1RSNSSHD	26 x 29 1/4 x 82 1/4	1940	1/4+	310
	2RSNHD	2RSNSAHD	2RSNSSHD	52 x 29 1/4 x 82 1/4	2560	1/3+	520
	3RSNHD	3RSNSAHD	3RSNSSHD	78 x 29 1/4 x 82 1/4	4010	1/2	725

## Standard Pass-Thru Models

FULL DOORS	1RNPT	1RNSAPT	1RNSSPT	26 x 39 x 82 1/4	1940	1/4+	340
	2RNPT	2RNSAPT	2RNSSPT	52 x 39 x 82 1/4	2560	1/3+	580
	3RNPT	3RNSAPT	3RNSSPT	78 x 39 x 82 1/4	4010	1/2	815
HALF DOORS	1RNPTH	1RNSAPTH	1RNSSPTH	26 x 39 x 82 1/4	1940	1/4+	340
	2RNPTH	2RNSAPTH	2RNSSPTH	52 x 39 x 82 1/4	2560	1/3+	580
	3RNPTH	3RNSAPTH	3RNSSPTH	78 x 39 x 82 1/4	4010	1/2	815

## Slim Line Reach-In Models

FULL DOORS	1RSEN	1RSENSA	1RSENSS	17 3/4 x 35 3/8 x 82 1/4	1940	1/4+	310
	2RSEN	2RSENSA	2RSENSS	36 1/4 x 35 3/8 x 82 1/4	2190	1/3+	430
HALF DOORS	1RSENHD	1RSENSAHD	1RSENSSHD	17 3/4 x 35 3/8 x 82 1/4	1940	1/4+	310
	2RSENHD	2RSENSAHD	2RSENSSHD	36 1/4 x 35 3/8 x 82 1/4	2190	1/3+	430
FULL DOORS SHALLOW DEPTH	1RSESN	1RSENSA	1RSESNSS	17 3/4 x 29 1/4 x 82 1/4	1940	1/4+	310
	2RSESN	2RSENSA	2RSESNSS	36 1/4 x 29 1/4 x 82 1/4	2190	1/3+	430
HALF DOORS SHALLOW DEPTH	1RSESNHD	1RSENSAHD	1RSESNSSH	17 3/4 x 29 1/4 x 82 1/4	1940	1/4+	310
	2RSESNHD	2RSENSAHD	2RSESNSSH	36 1/4 x 29 1/4 x 82 1/4	2190	1/3+	430

\*BTU/HR Rating @ +25°F, 90°F ambient. 10 ft. cord and plug attached

\*\*Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

## Specifications - Extra Wide Refrigerators

### Extra-Wide Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1REN	1RENSA	1RENSS	28 1/2 x 35 3/8 x 82 1/4	1940	1/4+	330
	1RXN	1RXNSA	1RXNSS	36 1/4 x 35 3/8 x 82 1/4	2190	1/3+	430
	2REN	2RENSA	2RENSS	57 x 35 3/8 x 82 1/4	2560	1/3+	560
	3REN	3RENSA	3RENSS	85 1/2 x 35 3/8 x 82 1/4	4010	1/2	785
HALF DOORS	1RENHD	1RENSAHD	1RENSSHD	28 1/2 x 35 3/8 x 82 1/4	1940	1/4+	330
	1RXNHD	1RXNSAHD	1RXNSSHD	36 1/4 x 35 3/8 x 82 1/4	2190	1/3+	430
	2RENHD	2RENSAHD	2RENSSHD	57 x 35 3/8 x 82 1/4	2560	1/3+	560
	3RENHD	3RENSAHD	3RENSSHD	85 1/2 x 35 3/8 x 82 1/4	4010	1/2	785
FULL DOORS SHALLOW DEPTH	1RESN	1RESNSA	1RESNSS	28 1/2 x 29 1/4 x 82 1/4	1940	1/4+	310
	1RXSN	1RXSNSA	1RXSNSS	36 1/4 x 29 1/4 x 82 1/4	2190	1/3+	410
	2RESN	2RESNSA	2RESNSS	57 x 29 1/4 x 82 1/4	2560	1/3+	520
	3RESN	3RESNSA	3RESNSS	85 1/2 x 29 1/4 x 82 1/4	4010	1/2	725
HALF DOORS SHALLOW DEPTH	1RESNHD	1RESNSAHD	1RESNSSHD	28 1/2 x 29 1/4 x 82 1/4	1940	1/4+	310
	1RXSNHD	1RXSNSAHD	1RXSNSSHD	36 1/4 x 29 1/4 x 82 1/4	2190	1/3+	410
	2RESNHD	2RESNSAHD	2RESNSSHD	57 x 29 1/4 x 82 1/4	2560	1/3+	520
	3RESNHD	3RESNSAHD	3RESNSSHD	85 1/2 x 29 1/4 x 82 1/4	4010	1/2	725

### Extra-Wide Pass-Thru Models

FULL DOORS	1RENPT	1RENSAPT	1RENSSPT	28 1/2 x 38 3/4 x 82 1/4	1940	1/4+	360
	1RXNPT	1RXNSAPT	1RXNSSPT	36 1/4 x 38 3/4 x 82 1/4	2190	1/3+	435
	2RENPT	2RENSAPT	2RENSSPT	57 x 38 3/4 x 82 1/4	2560	1/3+	620
	3RENPT	3RENSAPT	3RENSSPT	85 1/2 x 38 3/4 x 82 1/4	4010	1/2	875
HALF DOORS	1RNPTH	1RENSAPTH	1RENSSPTH	28 1/2 x 38 3/4 x 82 1/4	1940	1/4+	360
	1RXNPTH	1RXNSAPTH	1RXNSSPTH	36 1/4 x 38 3/4 x 82 1/4	2190	1/3+	435
	2RENPTH	2RENSAPTH	2RENSSPTH	57 x 38 3/4 x 82 1/4	2560	1/3+	620
	3RENPTH	3RENSAPTH	3RENSSPTH	85 1/2 x 38 3/4 x 82 1/4	4010	1/2	875

\*BTU/HR Rating @ +25°F, 90°F ambient. 10 ft. cord and plug attached

\*\*Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

## Specifications - Standard & Slim Line Freezers (0°F)

### Standard Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1FN	1FNSA	1FNSS	26 x 35 3/8 x 82 1/4	1590	1/2	325
	2FN	2FNSA	2FNSS	52 x 35 3/8 x 82 1/4	2470	1/2	555
	3FN	3FNSA	3FNSS	78 x 35 3/8 x 82 1/4	3575	3/4 <sup>§</sup>	790
HALF DOORS	1FNHD	1FNSAHD	1FNSSHHD	26 x 35 3/8 x 82 1/4	1590	1/2	325
	2FNHD	2FNSAHD	2FNSSHHD	52 x 35 3/8 x 82 1/4	2470	1/2	555
	3FNHD	3FNSAHD	3FNSSHHD	78 x 35 3/8 x 82 1/4	3575	3/4 <sup>§</sup>	790
FULL DOORS SHALLOW DEPTH	1FSN	1FSNSA	1FSNSS	26 x 29 1/4 x 82 1/4	1590	1/2	325
	2FSN	2FSNSA	2FSNSS	52 x 29 1/4 x 82 1/4	2470	1/2	555
	3FSN	3FSNSA	3FSNSS	78 x 29 1/4 x 82 1/4	3575	3/4 <sup>§</sup>	790
HALF DOORS SHALLOW DEPTH	1FSNHD	1FSNSAHD	1FSNSSHD	26 x 29 1/4 x 82 1/4	1590	1/2	325
	2FSNHD	2FSNSAHD	2FSNSSHD	52 x 29 1/4 x 82 1/4	2470	1/2	555
	3FSNHD	3FSNSAHD	3FSNSSHD	78 x 29 1/4 x 82 1/4	3575	3/4 <sup>§</sup>	790

### Standard Pass-Thru Models

FULL DOORS	1FNPT	1FNSAPT	1FNSSPT	26 x 39 x 82 1/4	1590	1/3	355
	2FNPT	2FNSAPT	2FNSSPT	52 x 39 x 82 1/4	2470	3/4 <sup>§</sup>	665
HALF DOORS	1FNPTHD	1FNSAPTHD	1FNSSPTH	26 x 39 x 82 1/4	1590	1/3	355
	2FNPTHD	2FNSAPTHD	2FNSSPTH	52 x 39 x 82 1/4	2470	3/4 <sup>§</sup>	665

### Slim Line Reach-In Models

FULL DOORS	1FSEN	1FSENSA	1FSENSS	17 3/4 x 35 3/8 x 82 1/4	1590	1/2	305
	2FSEN	2FSENSA	2FSENSS	36 1/4 x 35 3/8 x 82 1/4	1840	1/2	445
HALF DOORS	1FSENHD	1FSENSAHD	1FSENSSHD	17 3/4 x 35 3/8 x 82 1/4	1590	1/2	305
	2FSENHD	2FSENSAHD	2FSENSSHD	36 1/4 x 35 3/8 x 82 1/4	1840	1/2	445
FULL DOORS SHALLOW DEPTH	2FSESN	2FSESNSA	2FSESNSS	36 1/4 x 29 1/2 x 82 1/4	1840	1/2	445

BTU/HR Rating @ -15°F, 90°F ambient  
10 ft. cord and plug attached (115-60-1 volts)

<sup>§</sup>No cord and plug attached (115/208-230-60-1 volts)

\*\*Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

## Specifications - Extra Wide Freezers (0°F)

### Extra-Wide Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1FEN	1FENSA	1FENSS	28 1/2 x 35 3/8 x 82 1/4	1590	1/2	345
	1FXN	1FXNSA	1FXNSS	36 1/4 x 35 3/8 x 82 1/4	1840	1/2	485
	2FEN	2FENSA	2FENSS	57 x 35 3/8 x 82 1/4	2470	1/2	595
	3FEN	3FENSA	3FENSS	85 1/2 x 35 3/8 x 82 1/4	3575	3/4 <sup>§</sup>	830
HALF DOORS	1FENHD	1FENSAHD	1FENSSHHD	28 1/2 x 35 3/8 x 82 1/4	1590	1/2	345
	1FXNHD	1FXNSAHD	1FXNSSHD	36 1/4 x 35 3/8 x 82 1/4	1840	1/2	485
	2FENHD	2FENSAHD	2FENSSHHD	57 x 35 3/8 x 82 1/4	2470	1/2	595
	3FENHD	3FENSAHD	3FENSSHHD	85 1/2 x 35 3/8 x 82 1/4	3575	3/4 <sup>§</sup>	830
FULL DOORS SHALLOW DEPTH	1FESN	1FESNSA	1FESNSS	28 1/2 x 29 1/4 x 82 1/4	1590	1/2	345
	1FXSN	1FXSNSA	1FXSNSS	36 1/4 x 29 1/4 x 82 1/4	1840	1/2	485
	2FESN	2FESNSA	2FESNSS	57 x 29 1/4 x 82 1/4	2470	1/2	595
	3FESN	3FESNSA	3FESNSS	85 1/2 x 29 1/4 x 82 1/4	3575	3/4 <sup>§</sup>	830
HALF DOORS SHALLOW DEPTH	1FESNHD	1FESNSAHD	1FESNSSHD	28 1/2 x 29 1/4 x 82 1/4	1590	1/2	345
	1FXSNHD	1FXSNSAHD	1FXSNSSHHD	36 1/4 x 29 1/4 x 82 1/4	1840	1/2	485
	2FESNHD	2FESNSAHD	2FESNSSHD	57 x 29 1/4 x 82 1/4	2470	1/2	595
	3FESNHD	3FESNSAHD	3FESNSSHD	85 1/2 x 29 1/4 x 82 1/4	3575	3/4 <sup>§</sup>	830

### Extra-Wide Pass-Thru Models

FULL DOORS	1FENPT	1FENSAPT	1FENSSPT	28 1/2 x 38 3/8 x 82 1/4	1590	1/3	375
	1FXNPT	1FXNSAPT	1FXNSSPT	36 1/4 x 38 3/8 x 82 1/4	1840	1/2	450
	2FENPT	2FENSAPT	2FENSSPT	57 x 38 3/8 x 82 1/4	3575	3/4 <sup>§</sup>	695
	3FE-PT	3FE-SA-PT	3FE-SS-PT	85 1/2 x 38 3/8 x 85 3/4	4325	1 <sup>§</sup>	945
HALF DOORS	1FENPTHHD	1FENSAPTHHD	1FENSSPTHHD	28 1/2 x 38 3/8 x 82 1/4	1590	1/3	375
	1FXNPTHHD	1FXNSAPTHHD	1FXNSSPTHHD	36 1/4 x 38 3/8 x 82 1/4	1840	1/2	450
	2FENPTHHD	2FENSAPTHHD	2FENSSPTHHD	57 x 38 3/8 x 82 1/4	3575	3/4 <sup>§</sup>	695

BTU/HR Rating @ -15°F, 90°F ambient  
 10 ft. cord and plug attached (115-60-1 volts)  
 §No cord and plug attached (115/208-230-60-1 volts)

\*\*Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

# Specifications - Dual Temperature

## Dual Temperature Standard Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	2RFN	2RFNSA	2RFNSS	52 x 35 3/8 x 82 1/4	1940, 1590	1/4, 1/3	580
	3RRFN	3RRFNSA	3RRFNSS	78 x 35 3/8 x 82 1/4	2560, 1590	1/3, 1/3	835
	3RFFN	3RFFNSA	3RFFNSS	78 x 35 3/8 x 82 1/4	1940, 2470	1/4, 1/2	835
HALF DOORS	1RFNHD	1RFNSAHD	1RFNSSHD	26 x 35 3/8 x 82 1/4	1625, 1800	1/5, 1/3	420
	2RFNHD	2RFNSAHD	2RFNSSHD	52 x 35 3/8 x 82 1/4	1940, 1590	1/4, 1/3	580
	3RRFNHD	3RRFNSAHD	3RRFNSSHD	78 x 35 3/8 x 82 1/4	2560, 1590	1/3, 1/3	835
	3RFFNHD	3RFFNSAHD	3RFFNSSHD	78 x 35 3/8 x 82 1/4	1940, 2470	1/4, 1/2	835

## Dual Temperature Extra-Wide Reach-In Models

FULL DOORS	2RFEN	2RFENSA	2RFENSS	57 x 35 3/8 x 82 1/4	1940, 1590	1/4, 1/3	620
HALF DOORS	1RFENHD	1RFENSAHD	1RFENSSHD	28 1/2 x 35 3/8 x 82 1/4	1625, 1800	1/5, 1/3	435
	1RFENHD	1RFENSAHD	1RFENSSHD	36 1/4 x 35 3/8 x 82 1/4	1940, 1590	1/4, 1/3	555
	2RFENHD	2RFENSAHD	2RFENSSHD	57 x 35 3/8 x 82 1/4	1940, 1590	1/4, 1/3	620

**Note:** Consult factory for Pass-Thru and Shallow Depth models.

BTU/HR Rating @ +25°F, 90°F ambient (refrigerators)

BTU/HR Rating @ -15°F, 90°F ambient (freezers)

(2) 10 ft. cords and plugs attached (115-60-1 volts)

\*\*Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

## Specifications - Standard & Extra Wide Display Refrigerators w/ Hinged Glass Doors

### Standard Reach-In Models w/ Hinged Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1RNGD	1RNSAGD	1RNSSGD	26 x 35 3/8 x 82 1/4	1940	1/4+	315
	2RNGD	2RNSAGD	2RNSSGD	52 x 35 3/8 x 82 1/4	2560	1/3+	530
	3RNGD	3RNSAGD	3RNSSGD	78 x 35 3/8 x 82 1/4	4010	1/2	740
HALF DOORS	1RNGDHD	1RNSAGDHD	1RNSSGDHD	26 x 35 3/8 x 82 1/4	1940	1/4+	315
	2RNGDHD	2RNSAGDHD	2RNSSGDHD	52 x 35 3/8 x 82 1/4	2560	1/3+	530
	3RNGDHD	3RNSAGDHD	3RNSSGDHD	78 x 35 3/8 x 82 1/4	4010	1/2	740
FULL DOORS SHALLOW DEPTH	1RSNGD	1RSNSAGD	1RSNSSGD	26 x 29 1/4 x 82 1/4	1940	1/4+	315
	2RSNGD	2RSNSAGD	2RSNSSGD	52 x 29 1/4 x 82 1/4	2560	1/3+	530
HALF DOORS SHALLOW DEPTH	1RSNGDHD	1RSNSAGDHD	1RSNSSGDHD	26 x 29 1/4 x 82 1/4	1940	1/4+	315
	2RSNGDHD	2RSNSAGDHD	2RSNSSGDHD	52 x 29 1/4 x 82 1/4	2560	1/3+	530

### Extra-Wide Reach-In Models w/ Hinged Glass Doors

FULL DOORS	1RENGD	1RENSAGD	1RENSSGD	28 1/2 x 35 3/8 x 82 1/4	1940	1/4+	335
	1RXNGD	1RXNSAGD	1RXNSSGD	36 1/4 x 35 3/8 x 82 1/4	2560	1/3+	440
	2RENGD	2RENSAGD	2RENSSGD	57 x 35 3/8 x 82 1/4	2560	1/3+	575
	3RENGD	3RENSAGD	3RENSSGD	85 1/2 x 35 3/8 x 82 1/4	3400	1/2	800
HALF DOORS	1RENGDHD	1RENSAGDHD	1RENSSGDHD	28 1/2 x 35 3/8 x 82 1/4	1940	1/4+	335
	1RXNGDHD	1RXNSAGDHD	1RXNSSGDHD	36 1/4 x 35 3/8 x 82 1/4	2560	1/3+	440
	2RENGDHD	2RENSAGDHD	2RENSSGDHD	57 x 35 3/8 x 82 1/4	2560	1/3+	575
	3RENGDHD	3RENSAGDHD	3RENSSGDHD	85 1/2 x 35 3/8 x 82 1/4	3400	1/2	800
FULL DOORS SHALLOW DEPTH	1RESNGD	1RESNSAGD	1RESNSSGD	28 1/2 x 29 1/4 x 82 1/4	1940	1/4+	335
	1RXSNGD	1RXNSAGD	1RXSNSSGD	36 1/4 x 29 1/4 x 82 1/4	2560	1/3+	440
	2RESNGD	2RESNSAGD	2RESNSSGD	57 x 29 1/4 x 82 1/4	2560	1/3+	575
HALF DOORS SHALLOW DEPTH	1RESNGDHD	1RESNSAGDHD	1RESNSSGDHD	28 1/2 x 29 1/4 x 82 1/4	1940	1/4+	335
	1RXSNGDHD	1RXNSAGDHD	1RXSNSSGDHD	36 1/4 x 29 1/4 x 82 1/4	2560	1/3+	440
	2RESNGDHD	2RESNSAGDHD	2RESNSSGDHD	57 x 29 1/4 x 82 1/4	2560	1/3+	575

**Note:** Consult factory for Pass-Thru and Shallow Depth models.

BTU/HR Rating @ +25°F, 90°F ambient

10 ft. cord and plug attached (115-60-1 volts)

§No cord and plug attached (115/208-230-60-1 volts)

\*\*Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

## Specifications - Standard & Extra Wide Display Refrigerators w/ Sliding Glass Doors

### Standard Reach-In Display Refrigerators w/ Sliding Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	2RNSGD	2RNSASGD	2RNSSSGD	52 x 34 x 82 1/4	2560	1/3+	530
HALF DOORS	2RNSGDHD	2RNSASGDHD	2RNSSSGDHD	52 x 34 x 82 1/4	2560	1/3+	530
FULL DOORS SHALLOW DEPTH	2RSNSGD	2RSNSASGD	2RSNSSGD	52 x 27 7/8 x 82 1/4	2560	1/3+	530
HALF DOORS SHALLOW DEPTH	2RSNSGDHD	2RSNSASGDHD	2RSNSSGDHD	52 x 27 7/8 x 82 1/4	2560	1/3+	530

### Extra-Wide Reach-In Refrigerators w/ Sliding Glass Doors

FULL DOORS	2RENSGD	2RENSASGD	2RENSSSGD	57 x 34 x 82 1/4	2560	1/3+	575
HALF DOORS	2RENSGDHD	2RENSASGDHD	2RENSSSGDHD	57 x 34 x 82 1/4	2560	1/3+	575
FULL DOORS SHALLOW DEPTH	2RESNSGD	2RESNSASGD	2RESNSSGD	57 x 27 7/8 x 82 1/4	2560	1/3+	575
HALF DOORS SHALLOW DEPTH	2RESNSGDHD	2RESNSASGDHD	2RESNSSGDHD	57 x 27 7/8 x 82 1/4	2560	1/3+	575

BTU/HR Rating @ +25°F, 90°F ambient

10 ft. cord and plug attached (115-60-1 volts)

§No cord and plug attached (115/208-230-60-1 volts)

\*\*Ship weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

## Specifications - Standard & Extra Wide Display Freezer (0°F) w/ Hinged Glass Doors

### Standard Reach-In Models w/ Hinged Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	1FNGD	1FNSAGD	1FNSSGD	26 x 35 3/8 x 82 1/4	2470	1/2	330
	2FNGD	2FNSAGD	2FNSSGD	52 x 35 3/8 x 85 3/4	4325	1 <sup>§</sup>	565
	3FNGD	3FNSAGD	3FNSSGD	78 x 35 3/8 x 85 3/4	6050	1 1/2 <sup>§</sup>	805
HALF DOORS	1FNGDHD	1FNSAGDHD	1FNSSGDHD	26 x 35 3/8 x 82 1/4	2470	1/2	330
	2FNGDHD	2FNSAGDHD	2FNSSGDHD	52 x 35 3/8 x 85 3/4	4325	1 <sup>§</sup>	565
	3FNGDHD	3FNSAGDHD	3FNSSGDHD	78 x 35 3/8 x 85 3/4	6050	1 1/2 <sup>§</sup>	805
FULL DOORS SHALLOW DEPTH	1FSNGD	1FNSNSAGD	1FNSNSGD	26 x 29 1/4 x 82 1/4	2470	1/2	330
	2FSNGD	2FNSNSAGD	2FNSNSGD	52 x 29 1/4 x 85 3/4	4325	1 <sup>§</sup>	565
HALF DOORS SHALLOW DEPTH	1FSNGDHD	1FNSNSAGDHD	1FNSNSGDHD	26 x 29 1/4 x 82 1/4	2470	1/2	330
	2FSNGDHD	2FNSNSAGDHD	2FNSNSGDHD	52 x 29 1/4 x 85 3/4	4325	1 <sup>§</sup>	565

**Note:** Consult factory for Pass-Thru models.

### Extra-Wide Reach-In Models w/ Hinged Glass Doors

FULL DOORS	1FENGD	1FENSAGD	1FENSSGD	28 1/2 x 35 3/8 x 82 1/4	2470	1/2	345
	1FXNGD	1FXNSAGD	1FXNSSGD	36 1/4 x 35 3/8 x 82 1/4	2720	3/4 <sup>§</sup>	455
	2FENGD	2FENSAGD	2FENSSGD	57 x 35 3/8 x 85 3/4	4325	1 <sup>§</sup>	610
	3FENGD	3FENSAGD	3FENSSGD	85 1/2 x 35 3/8 x 85 3/4	6050	1 1/2 <sup>§</sup>	860
HALF DOORS	1FENGDHD	1FENSAGDHD	1FENSSGDHD	28 1/2 x 35 3/8 x 82 1/4	2470	1/2	345
	1FXNGDHD	1FXNSAGDHD	1FXNSSGDHD	36 1/4 x 35 3/8 x 82 1/4	2720	3/4 <sup>§</sup>	455
	2FENGDHD	2FENSAGDHD	2FENSSGDHD	57 x 35 3/8 x 85 3/4	4325	1 <sup>§</sup>	610
	3FENGDHD	3FENSAGDHD	3FENSSGDHD	85 1/2 x 35 3/8 x 85 3/4	6050	1 1/2 <sup>§</sup>	860
FULL DOORS SHALLOW DEPTH	1FESNGD	1FESNSAGD	1FESNSGD	28 1/2 x 29 1/2 x 82 1/4	2470	1/2	345
	1FXSNGD	1FXSNSAGD	1FXSNSGD	36 1/4 x 29 1/4 x 82 1/4	2720	3/4 <sup>§</sup>	455
HALF DOORS SHALLOW DEPTH	1FESNGDHD	1FESNSAGDHD	1FESNSGDHD	28 1/2 x 29 1/4 x 82 1/4	2470	1/2	345
	1FXSNGDHD	1FXSNSAGDHD	1FXSNSGDHD	36 1/4 x 29 1/4 x 82 1/4	2720	3/4 <sup>§</sup>	455

**Note:** Consult factory for Pass-Thru models.

BTU/HR Rating @ -15°F, 90°F ambient

10 ft. cord and plug attached (115-60-1 volts)

§No cord and plug attached (115/208-230-60-1 volts)

\*\*Ship weight for Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for shipping weight of these models.

- Chrome or stainless steel shelves
- Add'l epoxy-coated steel shelves
- Wine racks
- Heavy-duty pilaster strips (not available on all models)
- Pan slide assemblies (not available on all models)
- Adjustable legs
- Rehinging of doors (consult factory)
- Correctional facility package
- Expansion valve system (standard on some models)
- Custom laminates
- Stainless steel case back
- Glass door on Pass-Thru models (consult factory)

### Correctional Facility Package



Coverless hinges



Security screws



Locking hasp  
(lock not included)



Stainless steel mesh  
security cover

## Engineering, Manufacturing & Quality Control

Continental Refrigerator engineers and builds our Reach-Ins and Pass-Thrus to meet the most stringent specifications demanded by consultants and service operators. All cabinets are constructed of top quality materials and components, attributing to their genuine ruggedness and durability. Our Reach-Ins and Pass-Thrus are designed with enhancements to endure everyday use in typical commercial kitchen environments.


Prior to factory shipping, all models are performance-run tested for a minimum of 12 hours, providing a highly sophisticated temperature analysis recording, exclusive to each individual cabinet. This recording is then supplied, along with the unit's operation manual, for the customer. A final leak test, vibration check, noise level and visual examination is made by our quality control team, to assure a superior product is shipped from our factory.



Plug refrigeration air flow

### Air Flow

Air is drawn into the evaporator so condensation is not sprayed onto the food inside the cabinet. The conditioned air circulates radially from the evaporator compartment to provide more uniform air flow distribution.



Plug refrigeration system



Modular refrigeration system



Modular refrigeration air flow

### “Plug” Refrigeration

Pass-Thru Refrigerators and Freezers utilize a “plug” refrigeration system where the assembly is outside the food storage zone. The “plug” system can be removed for servicing, cleaning or converting from a refrigerator to freezer in the field.

### Modular Refrigeration

Reach-In Refrigerators and Freezers utilize a modular refrigeration system where the assembly is dropped into the food storage zone and uses an electric condensate evaporator which runs down the back of the unit. The modular system can be removed for servicing, cleaning or converting from a refrigerator to freezer in the field.

*Product design and specifications are subject to change without prior notice.*

## How to Buy

### LOCAL SALES REPRESENTATIVES

### STATES COVERED

Wyllie Marketing	Weymouth, MA	(781) 340-6157	<b>ME, RI, NH, MA, VT, CT</b>
Link 2 Hospitality Solutions	Rochester, NY	(585) 254-1780	<b>Upstate NY</b>
C.R. Peterson Associates	Avon, MA	(800) 257-4040	<b>N. NJ, New York City</b>
Schmid Dewland & Associates	Marlton, NJ	(856) 783-3400	<b>E. PA, DE, S. &amp; Central NJ</b>
Link 2 Hospitality Solutions	Bridgeville, PA	(412) 341-2020	<b>W. PA, W. VA (except Panhandle)</b>
High Sabatino Associates, Inc.	Jessup, MD	(301) 470-7051	<b>DC, MD, VA, W. VA (Panhandle)</b>
Stiefel Associates, Inc.	Lansing, MI	(517) 393-3019	<b>MI (except Upper Peninsula)</b>
Alliance Foodservice Equipment	Pickerington, OH	(800) 833-0797	<b>OH, KY</b>
Stiefel Associates, Inc.	Edinburgh, IN	(800) 832-6442	<b>IN</b>
Jay Mark Group, LTD	Elk Grove Village, IL	(847) 545-1918	<b>N. IL</b>
North Star Agency	Minneapolis, MN	(763) 545-1400	<b>MN, ND, SD</b>
Mirkovich & Associates	Waukesha, WI	(630) 792-0080	<b>WI, MI (Upper Peninsula)</b>
Select Marketing	St. Louis, MO	(314) 961-3332	<b>MO, KS, IA, NE, S. IL</b>
Premier Foodservice Group	Norcross, GA	(877) 667-2192	<b>NC, SC</b>
Pro-Quip Foodservice	Little Rock, AR	(501) 221-7120	<b>AR, LA, MS, W. TN (W. of Tenn. River)</b>
The Veitch Group	Ft. Lauderdale, FL	(954) 316-6162	<b>FL (except Panhandle)</b>
Merkolat	Pembroke Pines, FL	(864) 248-6260	<b>Latin America, Caribbean</b>
Premier Foodservice Group	Norcross, GA	(877) 667-2192	<b>AI, FL (Panhandle), GA, E. TN (E. of Tenn River)</b>
Desert Peak Marketing	Denver, CO	(303) 790-2424	<b>CO, S. ID, MT, UT WY</b>
Roller & Associates	Seattle, WA	(206) 547-3555	<b>WA, OR, AK, N. ID</b>
Foodservice Equipment Agents	Placentia, CA	(714) 693-3329	<b>AZ (Bull Head City), S. CA, S. NV</b>
Inform Foodservice Solutions	Walnut Creek, CA	(800) 655-7756	<b>N. CA, N. NV</b>
EMC Hospitality	Kealahou, HI	(808) 315-2077	<b>HI</b>
Desert Peak Marketing	Phoenix, AZ	(602) 255-0976	<b>AZ (except Bull Head City), NM, TX (El Paso)</b>
Forbes Hever & Wallace, Inc.	Coppell, TX	(972) 219-8898	<b>OK, TX (except El Paso)</b>



A Division of National Refrigeration & Air Conditioning Products

Continental Refrigerator | Local: (215) 244-1400  
539 Dunksferry Road | Toll Free: (800) 523-7138  
Bensalem, PA 19020 | Fax: (215) 244-9579

[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

# Continental<sup>®</sup>

## Refrigerator

INNOVATIVE DESIGNS FOR YOUR FOODSERVICE NEEDS



PROUDLY  
DESIGNED & ASSEMBLED  
IN THE U.S.A.